

Light Duty Commercial Ultra Low NOx High Input Energy Saver Gas Water Heater



Photo is of
U-75T-80R-3N

FEATURING:



The Ultra-Low NOx High Input Models Feature:

- **Bradford White ICON System™**—Intelligent gas control with proven millivolt powered technology and built-in piezo igniter. A standard, off the shelf thermopile converts heat energy from the pilot flame into electrical energy to operate the gas valve and microprocessor. No need for external electricity.
- **Enhanced Performance**—Proprietary algorithms provide tighter temperature differentials.
- **Advanced Temperature Control System**—Microprocessor constantly monitors and controls burner operation to maintain consistent and accurate water temperature levels.
- **Intelligent Diagnostics**—An exclusive green LED light prompts the installer during start-up and provides ten different diagnostic codes to assist in troubleshooting.
- **Pilot On Indication**—Flashing green LED provides positive indication that pilot is on.
- **Separate Immersed Thermowell**—High strength advanced polymer composite thermowell provides isolation between electric temperature sensor and surrounding water. No need to drain the tank when removing gas valve.
- **Ultra Low NOx Burner with Primary and Secondary Air Distribution Devices**—Ensures proper air to gas ratio for reduction of NOx generated by the combustion process.
- **Maintenance Free**—No regular cleaning of air inlet openings or flame arrestor is required under normal conditions.
- **Sight Window**—Offers a view into the combustion chamber to observe the operation of the pilot and burner.
- **Factory Installed Hydrojet 2™ Total Performance System**—Cold water inlet sediment reducing device helps prevent sediment build up in tank.
- **Vitraglas® Lining**—Bradford White tanks are lined with an exclusively engineered enamel formula that provides superior tank protection from the highly corrosive effects of hot water. This formula (Vitraglas®) is fused to the steel surface by firing at a temperature of over 1600°F (871°C).
- **More Precise Temperature Control**—With an adjustable temperature up to 180°F.
- **Side Connections**—3/4" NPT tapings allow an easy connection for space heating applications (potable water only).
- **Non-CFC Foam Insulation**—Covers the sides and top of tank, reducing the amount of heat loss. This results in less energy consumption, improved operation efficiencies and jacket rigidity.
- **Pedestal Base**—Rugged and durable base allows easy transport and positioning, while providing corrosion resistant contact with floor.
- **Water Connections**—Factory installed true dielectric fittings extend water heater life and ease installation (75T has 1" NPT and 100T has 1¼" NPT).
- **Protective Magnesium Anode Rod**—Provides added protection against corrosion for long trouble-free service.
- **Hand Hole Cleanout**—Allows inspection of tank interior and facilitates the removal of sediment deposits (optional on 75T models).
- **4" (107 mm) "Snap Lock" Draft Diverter**
- **T&P Relief Valve**—Included.
- **Low Restriction Brass Drain Valve**—Durable tamper proof design.
- **Design Certified by CSA International (formerly AGA and CGA).**
- **Complies with the latest ultra-low NOx requirement (14 ng/J NOx limit).**

3 or 5 Year Limited Tank Warranties / 1-Year Limited Warranty on Component Parts.

For more information on warranty, please visit www.bradfordwhite.com

For products installed in USA, Canada and Puerto Rico. Some states do not allow limitations on warranties. See complete copy of the warranty included with the heater.

Light Duty Commercial Ultra Low NOx High Input Gas Water Heater

Ultra Low NOx High Input Energy Saver Models

NATURAL GAS

Meet or exceed ASHRAE 90.1b (current standard) C.E.C. Listed
80% Thermal Efficiency


Model Number	Capacity		Recovery at 100°F Rise*	A Floor to Flue Conn.		B Jacket Dia.	C Vent Size	D Floor to T&P Conn.	E Floor to Gas Conn.	F Floor to Space Heating Return in.	G Floor to Space Heating Outlet in.	H Floor to Water Conn.	K Depth	L Floor to Top of Heater	Approx. Shipping Weight	
	U.S. Gal.	Imp. Gal.		Nat. BTU/Hr. Input	Nat. U.S. GPH											Nat. Imp. GPH
U-75T-80R-3N	75	63	76,000	74	62	64 ¹ / ₈	26	4	53 ³ / ₈	14 ³ / ₄	16 ¹ / ₂	53 ³ / ₈	61 ³ / ₈	30 ¹ / ₄	60 ¹ / ₈	269
U-100T-88R-3N	100	83	85,000	82	69	69 ¹³ / ₁₆	28 ¹ / ₄	4	60 ⁵ / ₈	16 ³ / ₄	19 ¹ / ₈	51 ¹³ / ₁₆	67 ⁷ / ₈	32 ¹ / ₂	66 ⁵ / ₈	401

Model Number	Capacity		Recovery at 56°C Rise*	A Floor to Flue Conn.		B Jacket Dia.	C Vent Size	D Floor to T&P Conn.	E Floor to Gas Conn.	F Floor to Space Heating Return mm.	G Floor to Space Heating Outlet mm.	H Floor to Water Conn.	K Depth	L Floor to Top of Heater	Approx. Shipping Weight
	Liters			Nat. kW Input	Nat. Liters/Hour										
U-75T-80R-3N	284		22.3	280	1629	610	102	1356	375	419	1356	1559	768	1527	122
U-100T-88R-3N	379		24.9	310	1753	718	102	1540	425	486	1319	1724	826	1692	182


Available in Natural Gas only.

For 5 year models, change suffix from "3" to "5".

*Based on manufacturers rated thermal efficiency.



Model U-75T-80R-3N



Model U-100T-88R-3N

All models comply with the latest ultra-low NOx requirements of 14 ng/J or less.

General

All gas water heaters are certified at 300 PSI test pressure (2068 kPa) and 150 PSI working pressure (1034 kPa). The 75 gallon model (284 liters) has 1" NPT (25mm) water connections on 11" (279mm) centers and 100 gallon model (379 liters) has 1 1/4" NPT (32mm) water connections on 16" (406mm) centers. All gas connections are 1/2" (13mm).

All models design certified by CSA International (formerly AGA/CGA), ANSI standard Z-21.10.3 and peak performance rated.

Dimensions and specifications subject to change without notice in accordance with our policy of continuous product improvement.

Suitable for Water (Potable) Heating and Space Heating.

Toxic chemicals, such as those used for boiler treatment, shall NEVER be introduced into this system. This unit may NEVER be connected to any existing heating system or component(s) previously used with a non-potable water heating appliance.



For U.S. and Canada field service, contact your professional installer or local Bradford White sales representative.

Sales 800-523-2931 • Fax 215-641-1670 / Technical Support 800-334-3393 • Fax 269-795-1089 • Warranty 800-531-2111 • Fax 269-795-1089

International: Telephone 215-641-9400 • Telefax 215-641-9750 / www.bradfordwhite.com

BRADFORD WHITE-CANADA INC. Sales / Technical Support 866-690-0961 / 905-238-0100 • Fax 905-238-0105 / www.bradfordwhite.com

Built to be the Best™

©2014, Bradford White Corporation. All rights reserved.